

NOP-210



Bluetooth Printer



Online retailers



Logistics



Storage



- Paper width 25-58mm, supports printing of multiple size labels
- Compact appearance and fresh color scheme. Paper calibration function, printing
- Stable cloud printer, remote and multi person shared printing can be achieved after WIFI network connection

NOP-210 Specifications

Print mode	Thermal sensitive	System support platform	Android
Resolving power	203dpi	Docking platform	platforms such as tomato tags, courier assistants, and Fenghuo delivery
Maximum printing speed	100mm/s	Firmware upgrade method	Support USB local upgrade and OTA upgrade
Print width range	Max 48mm	Device log retrieval	Not currently supported
Print length	25-175mm (removing watermark function can reach 300mm)	Equipment status reporting	feasible
Support paper types	Roll paper	Homework status reporting	feasible
Width	25-58mm	Paper cutting method	Manual paper tearing
Outer diameter of paper roll	≤80mm	Opening method	Flip up the cover
Medium thickness	0.08-0.2mm	Paper warehouse form	Paper bin diameter 80mm
Processor	32-bit RISCCPU	Paper output method	Take out the paper
Storage	RAM:2MB FLASH:8MB	Appearance size (Length * Width * Height)	160*120*122mm
Communication interface	USB(Optional:Bluetooth, Wi-Fi)	Packaging size	198*180*140mm
Electrical parameters	DC9V,2A	Bare Weight	420g(including battery/adapter)
Print head brand	ROHM	Weight of a single machine	0.78Kg
Movement lifespan	50KM	Parts	Power adapter, data cable, instruction manual (including warranty card)
Sensor type	Paper shortage, label stitching, cover opening, print head temperature	Number of units	12 units/box
Instruction set	TSPL、ESC	Key	Open lid button * 1, paper feed button * 1
Print contents	English, Simplified Chinese, Traditional Chinese, Images, Characters, Lines, Symbols, 1D Barcodes, 2D Barcodes	Voice prompt	Buzzer
Encoding method	GBK,BIG5,KSC5601,UTF-8(vector font)	Working temperature/humidity	0°C-40°C, 30%-80%RH
Font type	Song style	Storage temperature/humidity	-40°C-60°C, 5%-95%RH
Font size	ASCII Font A:12*24,ASC Font B: 9*17, Chinese characters 24 * 24	Paper rollback	Support (short distance)
One-dimensional code	EAN128,CODE128,CODE25,CODE39,CODE93,EAN13 EAN13+2,EAN13-5,CODABAR,POST,UPCA,UPCA+2 UPCA+5,UPCE+2,UPCE+5,PLESSEY,ITF14,EAN14	Auto feed	feasible
QR code	QRCODE,DataMatrix	Certification standards	CCC certification
Graphical	Support bitmap of different densities and download and print bitmap (maximum size of each bitmap is 64K, total size of bitmap is 256K)	ESD requirements	Contact discharge: Soil 4KV Air discharge: Soil 8KV



The configuration and parameters listed on the product page above are subject to the actual product and are subject to change without notice.

Tel: +86-755-86717417 Fax: +86-755-82790632 E-mail: sales@newpostech.com Web: www.newpostech.com